# **GP** Batteries

## Material Safety Data Sheet for GP Cylindrical Alkaline Battery

| Document Number: MAA100   | Revision:29   | Page 1 of 5 |
|---|---|-------------|
| IDENTITY (As Used on Label and List) Alkaline batteries 13A(LR20)/14A(LR14)/15A(LR6)/ | Note: Blank spaces are not permitted if any item information is available, the space must be market |             |
| 24A(LR03)/25A(LR8D425)/910A(LR1)  |   |             |
| Section 1- Identification   |   |             |
| Manufacturer's Name   | Emergency Telephone Number  |             |
| GPI International Ltd.  |   |             |
| Zhongyin (Ningbo) Battery Co., Ltd.   |   |             |
| Address (Number, Street, City State, and  | Telephone Number for information  |             |
| ZIP Code)   | 852-2484-3111   |             |
| 7/F, Building 16W, 16 Science Park West Date of prepared and revision                 |   |             |
|   | Avenue, Hong Kong Science Park, New 01 Jan, 2022  |             |
| Territories. H.K.   |   |             |

## Section 2 – Hazards Identification

Classification

NΔ

Signature of Prepare (optional)

## Section 3 – Composition/Information on Ingredients

| Ingredient                               | CAS#       | EINECS No. | Approximate Content (wt%) |               |               |               |               |                  |
|--|------------|------------|---------------------------|---------------|---------------|---------------|---------------|------------------|
| ingredient                               |            |            |                           | 24A<br>(LR03) | 14A<br>(LR14) | 13A<br>(LR20) | 910A<br>(LR1) | 25A<br>(LR8D425) |
| Manganese<br>Dioxide (MnO <sub>2</sub> ) | 1313-13-9  | 215-202-6  | 42.6                      | 40.9          | 40.6          | 41.8          | 34.2          | 36.0             |
| Zinc (Zn)                                | 7440-66-6  | 231-175-3  | 16.1                      | 14.8          | 16.0          | 17.4          | 13.5          | 17.0             |
| Water (H <sub>2</sub> O)                 | 7732-18-5  | 231-791-2  | 12.2                      | 11.7          | 11.0          | 11.1          | 9.5           | 6.5              |
| Potassium<br>Hydroxide (KOH)             | 1310-58-3  | 215-181-3  | 5.2                       | 4.8           | 7.0           | 7.0           | 4.2           | 1.3              |
| Graphite                                 | 7782-42-5  | 231-955-3  | 3.0                       | 1.7           | 3.2           | 3.4           | 3.0           | 2.3              |
| Brass                                    | 12597-71-6 | 603-111-8  | 2.4                       | 3.0           | 1.2           | 0.8           | 2.3           | 3.5              |
| Steel                                    | 7439-89-6  | 231-096-4  | 15.7                      | 20.4          | 18.6          | 16.3          | 29.5          | 30.0             |
| Ni-plating                               | 7440-02-0  | 231-111-4  | 0.3                       | 0.3           | 0.2           | 0.2           | 0.3           | 0.6              |
| Nylon-66                                 | 32131-17-2 | 608-706-6  | 1.6                       | 1.5           | 1.6           | 1.4           | 2.9           | 2.2              |
| Fiber                                    | None       | None       | 0.9                       | 0.9           | 0.6           | 0.6           | 0.6           | 0.6              |


#### **Section 4 – First Aid Measures**

First Aid Procedures

If electrolyte leakage occurs and makes contact with skin, wash with plenty of water immediately.

If electrolyte comes into contact with eyes, wash with copious amounts of water for fifteen (15) minutes and contact a physician.

If electrolyte vapors are inhaled, provide fresh air and seek medical attention if respiratory irritation develops. Ventilate the contaminated area.



# **GP** Batteries

# Material Safety Data Sheet for GP Cylindrical Alkaline Battery


Document Number: MAA100 Revision:29 Page 2 of 5

|                               |                         |                              |                        | J                         |
|-------------------------------|-------------------------|------------------------------|------------------------|---------------------------|
| Section 5 - Fire-Figh         | nting Measures          | <u> </u>                     |                        |                           |
| Flash Point (Method Used)     | Ignition Temp.          | Flammable Limits             | LEL                    | UEL                       |
| N.A.                          | N.A.                    | N.A.                         | N.A.                   | N.A.                      |
| Extinguishing Media           |                         | -                            | -1                     |                           |
| Carbon Dioxide, Dry           | Chemical or Foam e      | extinguishers                |                        |                           |
| Special Fire Fighting Proced  | ures                    |                              |                        |                           |
| N.A.                          |                         |                              |                        |                           |
| Unusual Fire and Explosion    | Hazards                 |                              |                        |                           |
| Do not dispose of batt        | ery in fire - may exp   | olode.                       |                        |                           |
| Do not short-circuit ba       | attery - may cause b    | urns.                        |                        |                           |
| Section 6 - Accident          | al Release Mea          | asures                       |                        |                           |
| Steps to Be Taken in Case Ma  | aterial is Released or  | r Spilled                    |                        |                           |
| Batteries that are leak       | kage should be hand     | led with rubber gloves.      |                        |                           |
| Avoid direct contact          | with electrolyte.       |                              |                        |                           |
| Wear protective cloth         | ning and a positive p   | ressure Self-Contained Bi    | eathing Apparatus (S   | SCBA).                    |
| Section 7 – Handling          | and Storage             |                              |                        |                           |
| Safe handling and storage adv | vice                    |                              |                        |                           |
| Batteries should be           | handled and stored      | carefully to avoid short cir | cuits.                 |                           |
| Do not store in disc          | orderly fashion or all  | ow metal objects to be mi    | xed with stored batter | ries.                     |
| Never disassemble             | a battery.              |                              |                        |                           |
| Do not breathe cell           | vapors or touch inte    | rnal material with bare ha   | nds.                   |                           |
| The cells and batter          | ries shall not be store | ed in high temperature, the  | maximum temperatu      | are allowed is 60°C for a |
| short period during           | the shipment, Other     | wise the cells maybe leak    | age and can result in  | shortened service life    |



# Material Safety Data Sheet for GP Cylindrical Alkaline Battery

| Document Number: MAA100                                   |                            |         | Revision:29 |                    | Page 3 of 5 |   |
|---|----------------------------|---------|-------------|--------------------|-------------|---|
|   | – Exposure Cor             |         | Person F    | Protection         |             |   |
| Occupationa   | l Exposure Limits:         | LTEP    |             | STEP               |             |   |
| N.A.  |                            |         | N.A.        |                    |             |   |
| Respiratory I   | Protection (Specify Ty     | pe)     |             |                    |             |   |
|   | 1                          | N.A.    |             |                    |             |   |
| Ventilation   | Local Exhausts             |         |             | Special            |             |   |
|   |                            | N.A.    |             |                    | N.A.        |   |
|   | Mechanical (Gener          | ral)    |             | Other              |             |   |
|   |                            | N.A.    |             |                    | N.A.        |   |
| Protective G  | loves                      |         |             | Eye Protection     |             |   |
|   | N.A.                       |         |             |                    | N.A.        |   |
| Other Protec  | tive Clothing or Equip     | ment    |             |                    |             |   |
|   | N.A.                       |         |             |                    |             |   |
| Work / Hygi   | enic Practices             |         |             |                    |             |   |
| ,, oiii, ii) 81   | N.A.                       |         |             |                    |             |   |
| Section 0   | - Physical / Che           | mical   | Droportio   | 6                  |             |   |
| Boiling Point   |                            | illicai |             | avity ( $H_2O=1$ ) |             |   |
|   | N.A.                       |         |             |                    | N.A.        |   |
| Vapor Pressu  | re (mm Hg)<br>N.A.         |         | Melting Poi | nt                 | N.A.        |   |
| Vapor Densit  |                            |         | Evaporation | Rate (Butyl Aceta  |             | _ |
|   | N.A.                       |         |             |                    | N.A.        |   |
| Solubility in   | Water<br>N.A.              |         |             |                    |             |   |
| Appearance a  |                            |         |             |                    |             |   |
| Section 1   | 0 Stability and            | I Doggi |             | al Shape, odorless |             |   |
| Stability   | 0 – Stability and Unstable | I NEACI | Conditions  | s to Avoid         |             |   |
|   |                            |         |             |                    |             |   |
|   | Stable                     | X       |             |                    |             |   |
| Incompatibili   | ty (Materials to Avoid     |         | I           |                    |             |   |
| Hazardona D   | ecomposition or Bypro      | duata   |             |                    |             |   |
| nazardous De  | ecomposition of Bypic      | ducts   |             |                    |             |   |
| Hazardous May Occur Conditions Polymerizati on Conditions |                            |         | s to Avoid  |                    |             |   |
|   | Will Not Occur             | X       |             |                    |             |   |
|   |                            |         |             |                    |             |   |





## Material Safety Data Sheet for GP Cylindrical Alkaline Battery

Document Number: MAA100 Revision:29 Page 4 of 5

| Section 11 – Toxicological Information  |                                 |                         |                        |        |  |
|---|---------------------------------|-------------------------|------------------------|--------|--|
| Route(s) of   | Inhalation?                     | Skin?                   | Inge                   | stion? |  |
| Entry   |                                 | N.A.                    | N.A.                   | N.A.   |  |
| Health Hazard (Acu  | te and Chronic) / Toxicolog     | ical information        |                        |        |  |
| In case of ele  | ectrolyte leakage, skin will be | e itchy when contamir   | ated with electrolyte. |        |  |
| In contact wi   | th electrolyte can cause seve   | ere irritation and chem | ical burns.            |        |  |
| Inhalation of electrolyte vapors may cause irritation of the upper respiratory tract and lungs. |                                 |                         |                        |        |  |

## Section 12 - Ecological Information

N.A.

## **Section 13 – Disposal Considerations**

Dispose of batteries according to government regulations.

## **Section 14 – Transportation Information**

In general, all batteries in all forms of transportation (ground, air, or ocean) must be packaged in a safe and responsible manner. Regulatory concerns from all agencies for safe packaging require that batteries be packaged in a manner that prevents short circuits and be contained in "strong outer packaging" that prevents spillage of contents. All original packaging for GP alkaline batteries has been designed to be compliant with these regulatory concerns.


Alkaline batteries (sometimes referred to as "Dry cell" batteries) are not listed as dangerous goods under the ADR European Agreement Concerning the International Carriage of Dangerous Goods by Road, the IMDG International Maritime Dangerous Goods Code, UN Dangerous Good Regulations, IATA Dangerous Goods Regulations 63<sup>rd</sup> edition, ICAO Technical Instructions and the U.S. hazardous materials regulations (49 CFR). These batteries are not subject to the dangerous goods regulations provided they meet the requirements contained in the following special provisions

| . Regulatory Body | Special Provisions           |
|-------------------|------------------------------|
| ADR               | Not regulated                |
| IMDG              | Not regulated                |
| UN                | Not regulated                |
| US DOT            | 49 CFR 172.102 Provision 130 |
| IATA              | A123                         |
| ICAO              | Not regulated                |

All GP alkaline batteries are packed in such a way to prevent short circuits or the generation dangerous quantities of heat and meet the special provisions listed above. In addition, the IATA Dangerous Goods Regulations and ICAO Technical Instructions require the words "not restricted" and the Special Provision number A123 be provided on the air waybill, when an air waybill is issued.

#### Section 15 – Regulatory Information

Special requirements according to local regulations.





## Material Safety Data Sheet for GP Cylindrical Alkaline Battery

Document Number: MAA100 Revision:29 Page 5 of 5

## Section 16 – Other Information

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

## Section 17 - Measures for fire extinction

In case of fire, it is permissible to use any class of extinguishing medium on these batteries or their packing material. Cool exterior of batteries if exposed to fire to prevent rupture.

Fire fighters should wear self-contained breathing apparatus.