

# **Building product declaration**

according to BPD associations' standardised format eBVD

2024-12-19 10:30:01

Flexilight BAS

# 1. COMPANY INFORMATION

### **BMI Sverige AB**

Company name:	Organisation number:
BMI Sverige AB	556013-0709
Address:	Contact person:
Pulpetgatan 20	Lars Åhsberg
E-mail:	Telephone:
lars.ahsberg@bmigroup.com	070-6045046
VAT number:	Website:
	https://bmisverige.se/
GLN:	DUNS:
Company was last saved	
2024-12-11 09:55:43	
Company's certification	
✓ ISO 9001 ISO 14001	
Other:	
Bitumentätskiktproduktionen i Malmö är certifierad enligt ISO 9001.	
Policies and guidelines	
The company has a code of conduct/policy/guidelines for dealing with the requirements	social responsibility in the supplier chain, including procedures for ensuring
This is third-party audited	
If yes, which if the following guidelines have you affiliated to or management	system you have implemented
UN guiding principles for companies and human rights	
ILO's eight core conventions	
OECD Guidelines for Multinational Enterprises	
✓ UN Global Compact	
ISO 26000	
Other policy guidelines	

### **Management system**

If you have a management system for corporate social responsibility, what out of the following is included in the work?

Mappir	ng
Risk ar	nalysis
Action	plan
Monito	pring
Sustainability	reporting guidelines:
Enligt Årsredo	ovisningslagen (1995:554)

### 2. ARTICLE INFORMATION

### **Document data**

ld:	Version:
C-SE556013070901-33	8
Created:	Last saved:
2024-12-18 16:00:32	2024-12-19 10:30:01
Changes relates to:	
3	
Ändrat namn.	
Flexilight BAS	
Flexilight BAS	
Article name:	
Flexilight BAS	
Article No/ID concept	

Article identity: GTIN 7391738014715

Article identity: VAT-ID SE10006458 01- 10 006 460

### Product group/Product group classification

Product group system	Product group id
BK04	01409

### Article description:

Flexilight underlagsduk används under falsade överläggsplattor (t ex takpannor av betong, tegel eller plåt) på underlag av trä. Duken fungerar som vattenavledande skikt enligt kraven i AMA Hus JSC.61. Klass UD2. Flexilight tillverkas i Sverige för våra specifika byggtraditioner och klimatförhållanden. Underlagsduken är åldringsbeständig och diffusionstät. Stommen är belagd med SBS-modifierad bitumen som gör produkten smidig att hantera även vid låga temperaturer. Under- och översida skyddas av en filt av polypropen. Flexilight BAS kan användas vid minst 6° taklutning. Den 1 m breda våden har en klisterkant av bitumen i kombination med en folierad infästningskant. Uppbyggnaden ger en klibb- och sandfri arbetsmiljö.

Declarations of performance:

Yes

Declaration of performance number:

060-1230

Other information:

### 3. CHEMICAL CONTENT

### Chemical content

Does the declaration apply to a product or chemical product?

product

Enter chemical content for the whole article. The concentration is calculated at component level according to the principle of "once an article always an article".

Is there a safety data sheet for the article?

Not applicable

Is there classification of the article?

Not applicable

If yes, indicate the classification of the product under Regulation (EC) No

-

Enter which version of the candidate list has been used (Year, month, day)

2024-11-07

The article is covered by the RoHS Directive:

Enter the weight of the article:

No

Enter how large a proportion of the material content has been declared [% ]:

100

If 100% material content is not declared, please state the reason

-

If the article contains nanomaterials deliberately added to obtain a particular function, enter these here:

Has the presence of nanomaterials deliberately added to notifiable chemical products been reported to the Product Register

No

Enter the proportion of volatile organic substances [g/litre], applies only to sealants, paints, varnishes and adhesives:

### Article and/or sub-components

Phase	Delivery		
Component	Bindemedel	Weight% of product	80 <x<85< th=""></x<85<>

### Comment

Material	Substance	Concentration interval (%)	EG/CAS/Alternative designation	Other substance properties
SBS modifierad asfalt		80 <x<85< td=""><td></td><td></td></x<85<>		
SBS modifierad asfalt	Bitumen destillerad	62 <x<66< td=""><td>8052-42-4</td><td></td></x<66<>	8052-42-4	
SBS modifierad asfalt	Bitumen oil (recycled)	10 <x<15< td=""><td>8052-42-4</td><td></td></x<15<>	8052-42-4	
SBS modifierad asfalt	SBS	5 <x<7< td=""><td>91261-65-3</td><td></td></x<7<>	91261-65-3	

Component	Skyddsfolie	Weight% of 2 <x<3 product<="" th=""></x<3>
-----------	-------------	--

### Comment

Material	Substance	Concentration interval (%)	EG/CAS/Alternative designation	Other substance properties
	Polyeten	1 <x<2< td=""><td>9002-88-4</td><td></td></x<2<>	9002-88-4	
	Polypropen	0.5 <x<1< td=""><td>9003-07-0</td><td></td></x<1<>	9003-07-0	

Component	Stomme	Weight% of 5 <x<7 product<="" td=""></x<7>

### Comment

Material	Substance	Concentration interval (%)	EG/CAS/Alternative designation	Other substance properties
Glasfiberfilt		3 <x<4< td=""><td></td><td><u> </u></td></x<4<>		<u> </u>
Glasfiberfilt	Glasfiber	3 <x<4< td=""><td>65997-17-3</td><td></td></x<4<>	65997-17-3	
PP-filt		3 <x<4< td=""><td></td><td></td></x<4<>		
PP-filt	Polypropen	3 <x<4< td=""><td>9003-07-0</td><td></td></x<4<>	9003-07-0	
Component	Ytskikt		Weight% of product	10 <x<12< td=""></x<12<>
Comment				
Material	Substance	Concentration interval (%)	EG/CAS/Alternative designation	Other substance properties
	PP-filt	10 <x<12< td=""><td>9003-07-0</td><td></td></x<12<>	9003-07-0	
Phase	Mounted			
Component	Bindemedel		Weight% of product	80 <x<85< td=""></x<85<>
Comment				
Material	Substance	Concentration interval (%)	EG/CAS/Alternative designation	Other substance properties
SBS modifierad asfalt		80 <x<85< td=""><td></td><td></td></x<85<>		
SBS modifierad asfalt	Bitumen destillerad	62 <x<66< td=""><td>8052-42-4</td><td></td></x<66<>	8052-42-4	
SBS modifierad asfalt	Bitumen oil (recycled)	10 <x<15< td=""><td>8052-42-4</td><td></td></x<15<>	8052-42-4	
SBS modifierad asfalt	SBS	5 <x<7< td=""><td>91261-65-3</td><td></td></x<7<>	91261-65-3	
Component	Stomme		Weight% of product	5 <x<7< td=""></x<7<>
Comment				
Material	Substance	Concentration interval (%)	EG/CAS/Alternative designation	Other substance properties
Glasfiberfilt		3 <x<4< td=""><td></td><td></td></x<4<>		
Glasfiberfilt	Glasfiber	3 <x<4< td=""><td>65997-17-3</td><td></td></x<4<>	65997-17-3	
PP-filt		3 <x<4< td=""><td></td><td></td></x<4<>		
PP-filt	Polypropen	3 <x<4< td=""><td>9003-07-0</td><td></td></x<4<>	9003-07-0	
Component	Ytskikt		Weight% of product	10 <x<12< td=""></x<12<>
Comment				
Material	Substance	Concentration interval (%)	EG/CAS/Alternative designation	Other substance properties
	PP-filt	10 <x<12< td=""><td>9003-07-0</td><td></td></x<12<>	9003-07-0	

Other information:

### 4. RAW MATERIALS

Is there supporting documentation for the raw materials for third-party certified system for control of origin, raw material extraction, manufacturing or recycling processes or similar (for example BES 6001:2008, EMS certificate, USGBC Program)? If yes, enter system(s):

### Raw materials

### Total recycled material in the article

Is recycled material included in the article?	
Material	
Polyesterbärare	
Share of waste (from own production)	Share of waste (from other people's production)
0	0
Recycled material (treated)	Recycled material
4	0
Weight/percent by weight	
>4 %	
Comment	

### Renewable material

Enter	proportion	of	renewable	material	in	the	article
	proportion	O1	TCTTCWabic	material		uic	articic

Included biobased raw material is tested according to ASTM test method D6866:

# Por this product, there has been no withdrawal of virgin fossil material Yes If yes, please indicate the maximum percentage of virgin fossil material that can be included in the material (or item) in question 96 Wood raw materials Wood raw materials are included Included wood raw material is certified How large a proportion is certified [%]? What certification system has been used (for example FSC, CSA, SFI with CoC, PEFC)? Reference number: Enter logging country for the wood raw material and that following criteria have been met. Country of logging: Does not contain type of wood or origin in CITES appendix of endangered species Which version of CITES has been used for the check?

## 5. ENVIRONMENTAL IMPACT

Environmental impact during life cycle of the article, production phase module A1-A3 under EN

		•	J	•	, <b>,</b>	•
<b>✓</b>	Has environmental p	roduct declaratio	n been dra	awn up according to	EN 15804 or ISO 14025 for	the article?
These	product-specific rule	s, known as PCR	, have bee	en applied:	Registration number / ID nu	mber for EPD:
The Ir	ternational EPD Syst	em PCR for Cons	struction P	roducts and CP	S-P-02107	
	e is environmental pro		or other lif	e cycle assessmer	t, describe how the environn	nental impact of the article is taken into account

# 6. DISTRIBUTION

### Distribution of finished article

No Does the supplier take back packaging for the article? No Is the supplier affiliated to a system for product responsibility for packaging? Yes If yes, which packaging and which system? Naringslivets Producentansvar (NPA) Can packaging/packaging be reused? No Can packaging/packaging be recycled? Yes Can packaging/packaging be energy recycled? Yes Does the supplier use Retursystem Byggpall? No Other information:  CONSTRUCTION PHASE Construction phase Does the article make special requirements in storage? Yes Specify Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullama i varmlager minst 24 timmar innan de arvänds. Max lagringshidt: 1 pall. Skyddas mot våta och direkt solljus. Does the article make special requirements for surrounding building products? No Specify	Does the supplier take back packaging for the article?  No Is the supplier affiliated to a system for product responsibility for packaging?  Yes If yes, which packaging and which system?  Nāringslivets Producentansvar (NPA) Can packaging/packaging be reused?  No Can packaging/packaging be recycled?  Yes Can packaging/packaging be energy recycled?  Yes Does the supplier use Retursystem Byggpall?  No Other information:  CONSTRUCTION PHASE Construction phase  Does the article make special requirements in storage?  Yes Specify Lastas och lagras stående. Vid temperaturer under -15°C (forvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot våta och direkt solljus.  Does the article make special requirements for surrounding building products?		the supplier apply any system with multiple-use packaging for the article?
Is the supplier affiliated to a system for product responsibility for packaging?  Yes  If yes, which packaging and which system?  Nāringslivets Producentansvar (NPA)  Can packaging/packaging be reused?  No  Can packaging/packaging be recycled?  Yes  Can packaging/packaging be energy recycled?  Yes  Does the supplier use Retursystem Byggpall?  No  Other information:  CONSTRUCTION PHASE  Construction phase  Does the article make special requirements in storage?  Yes  Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?	Is the supplier affiliated to a system for product responsibility for packaging?  Yes  If yes, which packaging and which system?  Naringslivets Producentansvar (NPA)  Can packaging/packaging be reused?  No  Can packaging/packaging be recycled?  Yes  Can packaging/packaging be energy recycled?  Yes  Can packaging/packaging be energy recycled?  Yes  Does the supplier use Retursystem Byggpall?  No  Other information:  CONSTRUCTION PHASE  Construction phase  Does the article make special requirements in storage?  Yes  Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de arvänds. Max lagringshid: 1 pall. Skyddas mot våla och direkt solljus.  Does the article make special requirements for surrounding building products?  No  Specify	No	
Is the supplier affiliated to a system for product responsibility for packaging?  Yes  If yes, which packaging and which system?  Nāringslivets Producentansvar (NPA)  Can packaging/packaging be reused?  No  Can packaging/packaging be recycled?  Yes  Can packaging/packaging be energy recycled?  Yes  Does the supplier use Retursystem Byggpall?  No  Other information:  CONSTRUCTION PHASE  Construction phase  Does the article make special requirements in storage?  Yes  Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de arvänds. Max lagringshight: 1 pail. Skyddas mot våta och direkt solljus.  Does the article make special requirements for surrounding building products?  No	Is the supplier affiliated to a system for product responsibility for packaging? Yes  If yes, which packaging and which system? Naringslivets Producentansvar (NPA) Can packaging/packaging be reused? No Can packaging/packaging be recycled? Yes Can packaging/packaging be energy recycled? Yes Does the supplier use Retursystem Byggpall? No Other information:  CONSTRUCTION PHASE Construction phase  Does the article make special requirements in storage? Yes Specify Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot vala och direkt scillus. Does the article make special requirements for surrounding building products? No Specify	Does	the supplier take back packaging for the article?
If yes, which packaging and which system?  Năringslivets Producentansvar (NPA)  Can packaging/packaging be reused?  No  Can packaging/packaging be recycled?  Yes  Can packaging/packaging be energy recycled?  Yes  Can packaging/packaging be energy recycled?  Yes  Does the supplier use Retursystem Byggpall?  No  Other information:  CONSTRUCTION PHASE  Construction phase  Does the article make special requirements in storage?  Yes  Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullama i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt soiljus.  No  No	If yes, which packaging and which system?  Naringslivets Producentansvar (NPA)  Can packaging/packaging be reused?  No  Can packaging/packaging be recycled?  Yes  Can packaging/packaging be energy recycled?  Yes  Does the supplier use Retursystem Byggpall?  No  Other information:  CONSTRUCTION PHASE  Construction phase  Does the article make special requirements in storage?  Yes  Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de arvänds. Max lagringshöjd: 1 pall. Skyddas mot våta och direkt soillus.  Does the article make special requirements for surrounding building products?  No  Specify	No	
If yes, which packaging and which system? Năringslivets Producentansvar (NPA) Can packaging/packaging be reused? No Can packaging/packaging be recycled? Yes Can packaging/packaging be energy recycled? Yes Does the supplier use Retursystem Byggpall? No Other information:  CONSTRUCTION PHASE Construction phase  Does the article make special requirements in storage? Yes Specify Lastas och lagras stäende. Vid temperaturer under -15°C forvaras rullama i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus. Does the article make special requirements for surrounding building products? No	If yes, which packaging and which system?  Năringslivets Producentansvar (NPA)  Can packaging/packaging be reused?  No  Can packaging/packaging be recycled?  Yes  Can packaging/packaging be energy recycled?  Yes  Does the supplier use Retursystem Byggpall?  No  Other information:  CONSTRUCTION PHASE  Construction phase  Does the article make special requirements in storage?  Yes  Specify  Lastas och lagras stäende. Vid temperaturer under -15°C forvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöid: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No  Specify	Is the	supplier affiliated to a system for product responsibility for packaging?
Naringslivets Producentansvar (NPA) Can packaging/packaging be reused? No Can packaging/packaging be recycled? Yes Can packaging/packaging be energy recycled? Yes Can packaging/packaging be energy recycled? Yes Does the supplier use Retursystem Byggpall? No Other information:  CONSTRUCTION PHASE Construction phase Does the article make special requirements in storage? Yes Specify Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus. Does the article make special requirements for surrounding building products? No	Näringslivets Producentansvar (NPA) Can packaging/packaging be reused? No Can packaging/packaging be recycled? Yes Can packaging/packaging be energy recycled? Yes Does the supplier use Retursystem Byggpall? No Other information:  CONSTRUCTION PHASE Construction phase  Does the article make special requirements in storage? Yes Specify Lastas ook lagras stående. Vid temperaturer under -15°C forvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus. Does the article make special requirements for surrounding building products? No Specify	Yes	
Can packaging/packaging be reused?  No Can packaging/packaging be recycled?  Yes Can packaging/packaging be energy recycled?  Yes Does the supplier use Retursystem Byggpall?  No Other information:  CONSTRUCTION PHASE Construction phase  Does the article make special requirements in storage?  Yes  Specify Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de anvånds. Max lagringshöjd: 1 pall. Skyddas mot våta och direkt solljus.  Does the article make special requirements for surrounding building products?  No	Can packaging/packaging be reused?  No Can packaging/packaging be recycled?  Yes Can packaging/packaging be energy recycled?  Yes Does the supplier use Retursystem Byggpall?  No Other information:  CONSTRUCTION PHASE Construction phase  Does the article make special requirements in storage?  Yes Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot våta och direkt solljus.  Does the article make special requirements for surrounding building products?  No Specify	If yes	, which packaging and which system?
Can packaging/packaging be recycled?  Yes  Can packaging/packaging be energy recycled?  Yes  Does the supplier use Retursystem Byggpall?  No  Other information:  CONSTRUCTION PHASE  Construction phase  Does the article make special requirements in storage?  Yes  Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot våta och direkt solljus.  Does the article make special requirements for surrounding building products?  No	No Can packaging/packaging be recycled? Yes Can packaging/packaging be energy recycled? Yes Does the supplier use Retursystem Byggpall? No Other information:  CONSTRUCTION PHASE Construction phase Does the article make special requirements in storage? Yes Specify Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshröjd: 1 pall. Skyddas mot väta och direkt solijus. Does the article make special requirements for surrounding building products? No Specify	Närin	gslivets Producentansvar (NPA)
Can packaging/packaging be recycled?  Yes  Can packaging/packaging be energy recycled?  Yes  Does the supplier use Retursystem Byggpall?  No  Other information:  CONSTRUCTION PHASE  Construction phase  Does the article make special requirements in storage?  Yes  Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot våta och direkt solljus.  Does the article make special requirements for surrounding building products?  No	Can packaging/packaging be recycled?  Yes  Can packaging/packaging be energy recycled?  Yes  Does the supplier use Retursystem Byggpall?  No  Other information:  CONSTRUCTION PHASE  Construction phase  Does the article make special requirements in storage?  Yes  Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt sollijus.  Does the article make special requirements for surrounding building products?  No  Specify	Can	packaging/packaging be reused?
Yes  Does the supplier use Retursystem Byggpall?  No  Other information:  CONSTRUCTION PHASE Construction phase  Does the article make special requirements in storage?  Yes  Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No	Yes  Does the supplier use Retursystem Byggpall?  No  Other information:  CONSTRUCTION PHASE Construction phase  Does the article make special requirements in storage?  Yes  Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No  Specify	No	
Can packaging/packaging be energy recycled?  Yes  Does the supplier use Retursystem Byggpall?  No  Other information:  CONSTRUCTION PHASE  Construction phase  Does the article make special requirements in storage?  Yes  Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No	Can packaging/packaging be energy recycled?  Yes  Does the supplier use Retursystem Byggpall?  No  Other information:  CONSTRUCTION PHASE Construction phase  Does the article make special requirements in storage?  Yes  Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No  Specify	Can	packaging/packaging be recycled?
Does the supplier use Retursystem Byggpall?  No Other information:  CONSTRUCTION PHASE Construction phase  Does the article make special requirements in storage?  Yes Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot våta och direkt solljus.  Does the article make special requirements for surrounding building products?  No	Poes the supplier use Retursystem Byggpall?  No Other information:  CONSTRUCTION PHASE Construction phase  Does the article make special requirements in storage?  Yes Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No Specify	Yes	
Does the supplier use Retursystem Byggpall?  No Other information:  CONSTRUCTION PHASE Construction phase  Does the article make special requirements in storage?  Yes Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No	Does the supplier use Retursystem Byggpall?  No Other information:  CONSTRUCTION PHASE Construction phase  Does the article make special requirements in storage?  Yes Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No Specify	Can	packaging/packaging be energy recycled?
Other information:  CONSTRUCTION PHASE Construction phase  Does the article make special requirements in storage?  Yes Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No	Other information:  CONSTRUCTION PHASE Construction phase Does the article make special requirements in storage?  Yes Specify Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No Specify	Yes	
CONSTRUCTION PHASE Construction phase Does the article make special requirements in storage?  Yes Specify Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No	CONSTRUCTION PHASE Construction phase  Does the article make special requirements in storage?  Yes Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No Specify	Does	the supplier use Retursystem Byggpall?
CONSTRUCTION PHASE Construction phase  Does the article make special requirements in storage?  Yes Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de anvånds. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No	CONSTRUCTION PHASE Construction phase  Does the article make special requirements in storage?  Yes  Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No  Specify	No	
Poes the article make special requirements in storage?  Yes  Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No	Construction phase  Does the article make special requirements in storage?  Yes  Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No  Specify	Othe	rinformation:
Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No	Specify  Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No  Specify	Coi	nstruction phase
Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No	Lastas och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No  Specify	Yes	
de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No	de används. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus.  Does the article make special requirements for surrounding building products?  No  Specify	Spec	
Does the article make special requirements for surrounding building products?  No	Does the article make special requirements for surrounding building products?  No  Specify		ny
No	No Specify	Lasta de ar	s och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan
Specify		de ar Does	is och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan nvänds. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus. the article make special requirements for surrounding building
	Other information:	de ar Does produ	is och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan nvänds. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus. the article make special requirements for surrounding building
	Other information:	de ar Does produ No	is och lagras stående. Vid temperaturer under -15°C förvaras rullarna i varmlager minst 24 timmar innan nvänds. Max lagringshöjd: 1 pall. Skyddas mot väta och direkt solljus. the article make special requirements for surrounding building ucts?

# 8. USE PHASE

### Use phase

9.

Does the article make requirements for input materials for operation and maintenance?
No
Specify:
Does the article require supply of energy during operation?
Not applicable
Specify:
Estimated technical service life for the article:
30-40 years
Comment:
Is there energy labelling under the Energy Labelling Directive (2010/30/EU) for the article?
Not applicable
If yes, enter labelling (G to A, A+, A+++, A+++):
If yes, enter marking (G to A)
Other information:
DEMOLITION
Demolition
Is the article prepared for disassembly (dismantling)?
Not applicable
Can the product be separated into pure material types for recycling?
No
Specify:
Does the article require special measures for protection of health and environment in demolition/disassembly?
No
Specify:
Other information:

# **10. WASTE MANAGEMENT**

### **Delivered article**

Is the supplied article covered by the Ordinance (2014:1075) on producer responsibility for electrical and electronic products when it becomes waste?
No
Is reuse possible for the whole or parts of the article when it becomes waste?
No
Specify:
Is material recovery possible for the whole or parts of the article when it becomes waste?
Yes
Specify:
Uttjänt/kasserad produkt är möjlig att återvinna genom omarbetning och inblandning i råvara för tillverkning av ny produkt.  Detta görs exempelvis i Holland. I vår produktionsanläggning omhändertas sedan 2014 allt produktionsspill och används som råvara för produktion av annan produkt.
Is energy recovery possible for the whole or parts of the article when it becomes waste?
Yes
Specify:
Uttjänt/kasserad produkt kan energiåtervinnas genom förbränning i godkänd förbränningsanläggning
Does the supplier have restrictions and recommendation for re-use, material or energy recovery or landfilling?
No
Specify:
Waste code for the delivered article when it becomes waste
170904 - 04 Annat blandat bygg- och rivningsavfall än det som anges i 17 09 01–17 09 03.
When the supplied article becomes waste, is it classified as hazardous waste?
No
Mounted article
Is the mounted article classified as hazardous waste?
No
Waste code for the mounted article
170904 - 04 Annat blandat bygg- och rivningsavfall än det som anges i 17 09 01–17 09 03.

### Other information

# 11. INDOOR ENVIRONMENT

### Indoor environment

mador environment									
The article is not intended for indoor use									
The article does not emit any substances									
Emissions from the article not measured									
Does the article have a critical moisture state?	Does the article have a critical moisture state?								
No									
If yes, state what:									
Noise	Electrical field	Magnetic fields							
Can the article give rise to own noise?	Can the article give rise to electrical fields?	Can the article give rise to magnetic fields?							
Not applicable	Not applicable	Not applicable							
Value:	Value:	Value:							
Unit:	Unit:	Unit:							
Measuring method:	Measuring method:	Measuring method:							
Paints and varnishes									
The article is resistant to fungi and algae in use in wet areas									
Emissions									

The article produces the following emissions in intended use:

### Other information